


AEC-NASA TECH BRIEF

Lawrence Berkeley Laboratory



AEC-NASA Tech Briefs announce new technology derived from the research and development program of the U.S. AEC or from AEC-NASA interagency efforts. They are issued to encourage commercial application. Tech Briefs are available on a subscription basis from the National Technical Information Service, Springfield, Virginia 22151. Requests for individual copies or questions relating to the Tech Brief program may be directed to the Technology Utilization Office, NASA, Code KT, Washington, D.C. 20546.

Stem Clutch for Motor Driven Valve



The problem:

During operation of the servo-motor driven needle valve, it is necessary to prevent the valve stem from being seized in either an open or a closed position. Such a seizure could damage the stem and possibly the motor as a result of overload. Although designs allow automatic programming of the motor operation, precise stopping of the motor is difficult.

The solution:

A mechanical clutch has been developed which introduces friction between the motor shaft and the needle valve when the latter is in danger of seizure.

How it's done:

In the present design, as shown in the figure, the needle-shaped valve is advanced into or withdrawn from

(continued overleaf)

This document was prepared under the sponsorship of the Atomic Energy Commission and/or the National Aeronautics and Space Administration. Neither the United States Government nor any person acting on behalf of the United States Government assumes any

liability resulting from the use of the information contained in this document, or warrants that the use of any information, apparatus, method, or process disclosed in this document may not infringe privately owned rights.

the valve seat by a rotatable threaded stem which is connected to the servo-motor. The motor shaft fits inside a sleeve, which is connected to the valve stem. When the motor shaft is turning and the valve stem stops rotating because the valve has closed, the pin in the spacer causes the spacer to overcome the friction provided by the Belleville spring and to slip. The amount of friction is easily adjusted by adjustment of the screw.

Notes:

1. Tests show that the clutch prevents overload in a valve using a 300 rpm servo-motor.

2. Requests for further information may be directed to:

Mr. Robert J. Morris Technical Information Division Lawrence Berkeley Laboratory University of California Berkeley, California 94720

Reference: B72-10345

Patent status:

No patent action is contemplated by AEC or NASA.

Source: Dwain E. Blum and Jean F. Wiltens Lawrence Berkeley Laboratory (LRL-10032)